



CFD investigation to quantify the effect of layered multiple miniature blades on the performance of Savonius rotor



Sonu Sharma*, Rajesh Kumar Sharma

Department of Mechanical Engineering, National Institute of Technology Hamirpur, HP 177005, India

ARTICLE INFO

Article history:

Received 9 February 2017

Received in revised form 10 April 2017

Accepted 17 April 2017

Keywords:

VAWT

CFD

Wind turbine

Savonius rotor

Turbulence

ABSTRACT

Present study is focussed on improvement of the coefficient of performance (COP) of a Savonius rotor using numerical simulation software. Quantification of the improvement is based on the comparison of the coefficient of performance (COP) of a basic configuration constituting a conventional Savonius rotor to that of a modified configuration developed by adding concentric multiple miniature blades inside the rotor blades of the basic configuration. Validation and grid convergence studies are carried out using $k - \epsilon$ and Shear Stress Transport (SST) turbulence models. Validation study suggested Shear Stress Transport (SST) model as more accurate and better option in present study. Shear Stress Transport (SST) turbulence model is used in the numerical simulations of the modified configuration. Optimum level of grid refinement is achieved through grid convergence study. Boundary layer mesh is created on the rotor blades, by estimating distance of first mesh node from the wall using desired values of y^+ for both $k - \epsilon$ and Shear Stress Transport (SST) turbulence models. An improvement in COP spanning between 8.1% and 11.34% is achieved with the modified configuration.

© 2017 Elsevier Ltd. All rights reserved.

1. Introduction

In recent decades, global concern over pollution, global warming and possible depletion of non-renewable sources of energy, such as oil has led to exploration of renewable and sustainable energy resources. Conventionally, wind energy is harnessed on large scale using Horizontal Axis Wind Turbines (HAWTs) spread over large area. But the application of Horizontal Axis Wind Turbines (HAWTs) is limited due to requirement of large wind velocities, high initial cost and large area required for their installation [1,2]. The use of unconventional methods of energy generation such as Savonius wind rotors in micro generation is growing, but it is still less widespread. The problem is that it has a low Coefficient of Performance (COP) [3–7]; theoretically $COP \cong 0.18$ [6]. Despite of low power generation capacity, Savonius rotors are gaining popularity among the decentralized power generation methods due to their simple assembly and high starting torque at small rotational speeds [3,8]; low operating costs [9]; easy installation, manufacturing and maintenance [4,9–12]. Savonius rotor is a brilliant design proposed by Finnish inventor S.J. Savonius [5,8,11,13]. Conventional Savonius rotors are drag type hydrokinetic Vertical Axis Wind Turbines (VAWTs). Savonius rotor has

low aerodynamic efficiency as compare to Darrieus type wind turbines [7,14]; but still preferable for many applications due to its good starting characteristics [4,15–17]. Also, as it is a VAWT, it can accept wind from any direction because of its omnidirectional characteristics and hence needs no yaw mechanism [7,8,11,17–19]. Many theoretical and experimental studies have been performed by various researchers in the past to improve the aerodynamic performance of the Savonius rotor [8]. Better performance can be achieved by using high aspect ratios [20]; low overlap ratios [21]; end plates [22]; two bladed Savonius rotor rather than three bladed [23]; deflector plate [12,24]; multiple quarter blades [25]. Improvement in the COP is desirable, without compromising the advantages of Savonius rotor and increasing the complexity of design [6].

A cost effective study can be performed using Computational Fluid Dynamics (CFD), saving material and manufacturing costs. The flow through and around the rotor is turbulent. It is very difficult to achieve accuracy in such highly turbulent and transient conditions, so the adopted methodology must be validated to ensure accuracy [6]. Also, turbulence being an important factor in analysis, the prediction of input values of turbulence parameters to be used in the numerical procedure must be done carefully.

Commercial CFD software, Ansys CFX 13 is used to carry out the numerical simulations. This choice was motivated by the availability of licenses for the use of software and the existing practice of its use in the research environment.

* Corresponding author.

E-mail address: esonusharma@gmail.com (S. Sharma).